

RF AMPLIFIER

MODEL *TM3098*

Available as: TM3098, 4 Pin TO-8 (T4)
 TN3098, 4 Pin Surface Mount (SM3)
 FP3098, 4 Pin Flatpack (FP4)
 BX3098, Connectorized Housing (H1L)

Features

- Superior Phase Noise Performance
- High Output Power: +30 dBm Typical
- Operating Temp. -55 °C to +85 °C
- Environmental Screening Available

Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency (MHz)	10 - 300 MHz	10 - 250 MHz
Gain (dB)	13.5	13 Min.
Power @ 1 dB Comp. (dBm)	+30	+29 Min.
Reverse Isolation (dB)	-17	-16 Max.
VSWR In	1.5:1	2.0:1 Max.
Out	1.5:1	2.0:1 Max.
Noise Figure (dB)	5.0	6.0 Max.
Power Vdc	+15	+15
mA	240	250 Max.

Note: Care should always be taken to effectively ground the case of each unit.


Typical Intermodulation Performance at 25 °C

Second Order Harmonic Intercept Point +66 dBm (Typ.)
 Second Order Two Tone Intercept Point +63 dBm (Typ.)
 Third Order Two Tone Intercept Point +45 dBm (Typ.)

Absolute Maximum (No Damage) Ratings

Ambient Operating Temperature -55°C to +100 °C
 Storage Temperature -62°C to +125 °C
 Case Temperature +125 °C
 DC Voltage +17 Volts
 Continuous RF Input Power +15 dBm
 Short Term RF Input Power 100 mW (1 Minute Max.)
 Maximum Peak Power 0.2 Watt (3 µsec Max.)

Typical Performance Data



Legend ——— +25 °C - - - - +85 °C ······ -55 °C

