

ANALOG LEVEL DETECTOR LNJ9901

PACKAGE: 4 Pin, 0.25" Sq. Surface Mount (SM12)

Features

- Wideband: Low VSWR
- Small Size
- Operating Temp. -40°C to 85°C
- Environmental Screening Available

Specifications




CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -40 °C to +85 °C
Frequency	20 - 2000 MHz	20 - 2000 MHz
VSWR (P _{IN} = 0 dBm)	1.25:1	1.8:1 Max.
Sensitivity (P _{IN} = 0 dBm)	+/-1.0	+/-0.8 Min.
Power	Vdc	+15
	mA	6
	Vdc	-15
	mA	6

Note: Care should always be taken to effectively ground the case of each unit.

Absolute Maximum (No Damage) Ratings

Ambient Operating Temperature -55°C to +125 °C
 Storage Temperature -62°C to +150 °C
 Case Temperature +125 °C
 DC Voltage +20 Volts
 Continuous RF Input Power +20 dBm

Typical Performance Data



Legend ——— + 25 °C - - - + 85 °C · · · · · -40 °C



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532

www.SpectrumMicrowave.com · Spectrum Microwave · 2707 Black Lake Place · Philadelphia, Pennsylvania 19154 · PH (215) 464-4000 · Fax (215) 464-4001