



TEMPEST 7975 VoIP Phone

The TEMPEST version of the Cisco 7975 VoIP phone is designed to grow with your organization and improve system capabilities. The settings keys allow the user to adjust display brightness, select background images, and ringer sounds to further enhance your conferencing experience.

The Emcon TEMPEST 7975 VoIP Phone also features a touchscreen display and a full-duplex speakerphone with acoustic echo cancellation. This phone is an ideal choice when security, resilience, and ease-of-use are essential.



Specifications

Codec Support

- G.711a, G.711u, G.729a, G729ab, G.722, and iLBC audio compression codecs are supported

Interface

- Two 100BaseFX-SC fast Ethernet fiber optic connections

Ethernet Switch

- Internal 2-port

Configuration Options

- IP address assignment can be statically configured or configured through the DHCP client

Fiber

- SC Primary interface and ST or MTRJ interface options

Environment

- Temperature: 32°F to 104°F
- Storage Temperature: 14°F to 140°F
- Humidity: 10% to 95% non-condensing

Physical Specifications

- Length: 27.9 cm (11")
- Width: 24.1cm (9.5")
- Height: 7.6 cm (3")
- Weight: 2.3 kg (5 lbs.)

Power

- Auto-ranging 110/220 VAC 50/60 Hz

Accreditations

- TEMPEST Level I - This terminal meets the requirements of: NSTISSAM TEMPEST/1-92, Level I; CID09/15A, Level I; and SDIP-27 Level A (providing the equipment and associated systems are installed to the requirements identified in SDIP-29).

